

# GASOILA® DEF



## Gasoila® DEF Soft-Set Thread Sealant For Diesel Exhaust Fluid

### GASOILA® DEF (Diesel Exhaust Fluid)

is a soft setting sealant for tough applications. Designed for systems carrying urea-based chemical reactant used in SCR systems (DEF).

- Excellent performance with systems handling Diesel Exhaust Fluid, 100% methanol, ethanol, alcohol and ideal for concentrated or dilute acids and caustic alkali, cutting oils, aromatic solvents, glycol/water solutions, coal tar, naphtha, ethylene glycol and ketones.
- NOT for use on ethanol blended gasoline. (Less than 100% ethanol)
- NOT for use on plastic pipe or oxygen.
- Use on thoroughly clean, dry threads.
- Temperature Range: -50°F to 450°F (-46°C to 234°C).
- Pressure Range: to 5,000 psi for gases; to 10,000 psi for liquids.
- One year shelf life when stored at 40°F to 80°F (5°C to 27°C).
- Use on epoxy type fiberglass pipe manufactured by A.O. Smith, Ameron, Fibercast and Antron.
- For use on NPT Threads.

**CAUTION:** Vapors flammable.  
Avoid heat and open flame.

FPC Stock Code	Container Size	Units per Case
DE04	1/4 pt. Brush	12




DE04

### GASOILA® DEF

- \* Mix product thoroughly prior to use.
- \* Apply to clean, dry threads.
- \* Assemble immediately.
- \* Allow 8-10 hours set up prior to use.

Gasoila DEF has excellent resistance to a wide variety of hard to seal chemicals. This single part product can be applied to clean and dry threads and immediately assembled.



**FEDERAL PROCESS  
CORPORATION**

4520 Richmond Road, Cleveland Ohio 44128  
216-464-6440 • 800-846-7325

**www.gasoila.com**

